

Robotic Arm CA10N



Features:

1. Top speed: By using light-weight arms and small sized motors, the fastest speed and acceleration is greatly enhanced. In addition, by adjusting acceleration of load and orientation, optimal continuous performance is fulfilled and cycle time is greatly reduced.
2. Tiny wrist and high torque: Compact wrist realizes free operation in narrow space. In addition, by adopting high output rotational torque and high rotating speed small-sized motors as well as enhancing wrist stiffness to raise the wrist loading capacity. The selection range of gripper, tool, and workpiece shape is also broadened.
3. Large area operation range: Besides maximum operation range, it also broadens the area of the all the axes. Thus expansion of the lower region and main body neighboring region action range is realized. The layout freedom is also raised.
4. Good environment adaptability: Each joint adopts double layer sealing structure and water proof interface so that the wrist part Ingress Protection Rating and basic axis Ingress Protection Rating reach IP67 and IP65 respectively.
5. High expandability: In the process of selecting accessories, built-in solenoid valve and detecting cable are applied so that the application of peripheral robotic arms, loading and unloading becomes easier. Moreover, standard cable bracket installation screw holes are configured in each axis of the robotic arm so that additional tubing and wiring can be achieved later on.

Product Specifications

Function		Description
Model		CA10N
Arm format		Vertical multi-joint
Controlled axes		6 Axis
Maximum payload (kg)		10Kg
Maximum motion range (°)	Rotation	±180°
	Horizontal arm	+145°~-105°
	Vertical arm	+150°~-163°
	Inner wrist	±270°



	Wrist bend	±145°
	Wrist turn	±360°
Maximum speed (°/sec.)	Rotation	250°/s
	Horizontal arm	250°/s
	Vertical arm	215°/s
	Inner wrist	365°/s
	Wrist bend	380°/s
	Wrist turn	700°/s
Allowable moment (N·m)	Inner wrist	22N·m
	Wrist bend	22N·m
	Wrist turn	10N·m
Allowable moment of inertia (kg·m ²)	Inner wrist	0.7kg·m ²
	Wrist bend	0.7kg·m ²
	Wrist turn	0.2kg·m ²
Repeatability (mm)		±0.04mm
Reach		1450mm
Resultant maximum speed		11800mm/s
Weight		150kg
Mounting positions		Floor, Top
Environment	Ambient temperature	0° ~ 45°C
	Relative humidity	35 ~ 85%, , non-condensing
IP Protection		Arm: IP67, Base: IP65
Power rating		5.6kVA
Corresponding controller		EC02

Ordering Information

Model No.	Descriptions
CA10N	Robotic arm CA10N



GOOGOL TECHNOLOGY (HK) LIMITED
Unit 1008-09, 10/F C-Bons International Center, 108
Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel.: +(852) 2358-1033
Fax: + (852) 2719-8399
E-mail: hkgoogol@gmail.com / sales@googoltech.com
Web: http://www.googoltech.com

GOOGOL TECHNOLOGY (SZ) LIMITED
Room W211, IER Building (PKU-HKUST High-
tech Industrial Park, Nanshan District, Shenzhen,
PRC (Postal Code: 518057)
Tel.: +(86) 755-26970817, 755-26970824,
Fax: +(86) 755-26970821
E-mail: googol@googoltech.com
Web: www.googoltech.com.cn

GOOGOL TECHNOLOGY (TWN) LIMITED
2F., No. 22, Ln. 10, Fuzhong 2nd St., Xitun
Dist., Taichung City 407, Taiwan
Tel.: +(886) 4-2358-8245
E-mail: twinfo@googoltech.com
Web: http://www.googoltech.com

www.googoltech.com

